

SCOPE

CFL SG 1610 Surge Generator



Locate Cable Faults Easily & Quickly With CFL Series ...

The Product

Fault occurrence on underground cables cannot be avoided due to many factors in prevailing conditions. Long outage of a cable from service results in heavy loss of revenue to the power distribution company, production loss to industries and unpleasant condition to consumers. Therefore, it is necessary to restore the supply in minimum possible time. This calls for appropriate instruments fulfilling all the requirement of the job.

Surge Generator is the backbone of underground cable fault locator test systems. Surge Generator is used with a Prelocator and SIM Filter for fault distance measurement and also used with Pin Pointer Set for pinpointing the exact fault spot.

SCOPE offers CFL SG 1610, Surge Generator with output of 16kV and 1000 Joules. It is ideal choice for fault location on all types of power cables from LV to EHV. CFL SG Series is equipped with different Protections, Interlocks and Auto-discharge Facility to ensure User Safety during operation. User Friendly controls, adequate form factor, contact free HV terminations makes this CFL SG Series most durable and best-designed sets in the segment.



Application

Prelocation of fault distance

- Impulse Current Method (ICM): Surge Generator applies HV Surge across the Faulty Core and Armour of the Cable, which creates a short circuit across the fault point. This momentarily short circuit produces Current Transients, captured by Current Coupler connected on the Return HV Path. These transients will be analysed on Prelocator connected to the Current Coupler, to calculate approximate Fault Distance.
- Secondary Impulse Method (SIM) : The Surge Generator plays vital role in conjunction with a SIM Filter and Prelocator instrument to produce arc at the fault point for short term. The standing arc at fault point facilitates easy and accurate fault distance measurement.

Pinpointing

Surge Generator can produce repetitive surges across the Faulty Core and Armour of the Cable, which will create Electromagnetic Field across the Cable Path and a thumping sound at fault point. These Electromagnetic and Acoustic Signals will be detected by Pinpointing Sensor (Ground Microphone) and Receiver with Headphones used to find exact fault point.

DC Hi-Pot Test (Optional Mode)

DC Hi-Pot test mode is used for safe and accurate measurement of leakage current to evaluate insulation integrity of the Device Under Test. This mode is very useful for testing Dielectric Withstand Capacity of Cable during the Manufacturing, Installation, Acceptance, Routine Repair and Maintenance. DC Hi-Pot mode is equipped with Settable Trip Current and Timer function. Also, DC Hi-Pot mode can be used to prelocate cable fault using Voltage Decay Method in conjunction with Prelocator.

Burn Down (Optional Mode)

Burn Down mode is used to alter the fault conditions to get the fault distance using Prelocator. It can be used to create a carbon bridge across high resistance nature fault in Paper Insulated cables and to dry the wet faults in Solid Extruded Cables for ease in Prelocation. In this mode DC High Voltage is applied across the Faulty Core and Armour of the Cable, a high amount of leakage current will be allowed to flow through the Cable. Due the I^2R effect at the fault point, generated heat / arc will modify the fault condition.

Sheath Fault Location (Optional Mode)

When outer PVC jacket of the Cable is damaged, Armour / Sheath of the Cable is exposed to the Mass of Earth, called as Sheath Faults. Sheath Fault Location Mode can be used to locate such faults with the help of D Frame Receiver. In this mode instrument injects DC Pulses into the Armour of the Cable with respect to Mass of Earth and this will creates a pool of potential on ground surface nearby to fault point and D Frame Receiver equipped with a Galvanometer detects the fault location.

Features

- Compact, Lightweight, and housed in rugged aluminum case
- Ideal choice for fault location on all type of power cables
- Backbone of Cable Fault Locator System
- Generates short duration high voltage surge for fault break down
- Built-in Current Coupler to determine the fault distance in conjunction with Prelocator unit
- Repetitive surges applied for pinpointing the exact fault location in conjunction Pinpointing set
- Supports SIM/ARM/MIM method for locating High resistance and flashing faults along with Prelocator and SIM Filter from CFL Series
- Available with optional modes such as DC Hi-Pot, Burn Down and Sheath Fault Location Mode
- Multiple options in a single instrument to avoid carrying several heavy instruments to the site
- Easy setup and intelligent protections make the high voltage testing safe & reliable
- Compatible with other models of SCOPE Make CFL Series

Benefits

Protections / Interlocks

- Variac Zero Interlock
- Input supply fuse protection
- Over Current Protection
- MCB trip control under overload condition
- Output Cable Plug Interlock
- Key Lock Switch
- Selection Switch Interlock
- Emergency OFF
- Over Temperature Protection
- Input Voltage Protection
- Earth OK Interlock
- Automatic discharge upon shutdown

Indications

- HV ON / OFF
- Overheat
- Error in settings*
- Variac Zero*
- Earth OK
- Manual Impulse
- I/P Voltage Error



*Applicable for Surge Generator with optional DC Modes

Specifications

Parameter	CFL SG 1610	
Output Voltage Ranges	0 - 4kV / 8kV / 16kV selectable	
Output Energy	Max. 1000J in each voltage range	
Impulse Sequence (Surge Rate)	Single Impulse (Manual) / 3 Sec / 6 Sec / 9 Sec or Single Impulse (Manual) / 2 Sec / 4 Sec / 8 Sec (Optional)	
Output Indication	Moving Coil Analog Meter for Output Voltage measurement Moving Coil Analog Meter for Leakage Current measurement in Optional DC Modes	
Measurement Accuracy	±5% of selected range	
Input Supply	230V AC ± 10%, 50/60Hz ± 10%, Single Phase, 1.2 kVA max.	
Cooling Type	Air Cooled	
Dimensions	Without DC Modes	680 x 480 x 660 mm
	With Optional DC Modes	835 x 810 x 880 mm
Weight (without trolley and test leads)	Without Optional DC Modes: 150kg approx. With Optional DC Modes: 155kg approx.	
Environmental (Operation)	0°C to 50°C, up to 95% RH (Non-Condensing)	
Environmental (Storage)	-10°C to 55°C, up to 95% RH (Non-Condensing)	

Optional DC Modes	Voltage	Current	Timer / Pulse Ratio*
Hi-Pot	0-16kV	3 / 6 / 12mA	5/10/15min
Burn Down	0-4 / 8 / 16kV	90 / 60 / 30mA	3min
Sheath Fault	0-8kV	60mA	*3/6/9s ON & 100ms OFF

SCOPE of Supply

Items		Test Lead Set Configuration			
		5m TLS	10m TLS	25m TLS	50m TLS
	CFL SG 1610 mounted on wheels	1 No	1 No	1 No	1 No
	1 x HV Output Cable	5m	10m	25m	50m
	1 x Auxiliary Earth Cable with Spike	10m	10m	10m	10m
	1 x Master Earthing Cable	5m	10m	25m	50m
	1 x Mains Supply Cable	5m	5m	5m	5m
	1 x D Frame with Soft Bag (Applicable for Sheath Fault Location Mode)	Optional	Optional	Optional	Optional
	1 x Cable Drum (Manual/Motorised)	Optional	Optional	Optional	Optional
	Test Lead Set (as per Order Code) with Carrying Case	1 No	1 No	1 No	1 No
	Factory Test & Calibration Report	1 No	1 No	1 No	1 No
	Operation Manual	1 No	1 No	1 No	1 No
	Spare Fuse Set	1 Set	1 Set	1 Set	1 Set



CFL SG 1610 without Optional DC mode



CFL SG 1610 with Optional DC mode

Ordering Code

Example: CFL SG 1610

N N C 2 F N F N T R I N #

CFL SG 1610

F F

N None*												Customized	Z
A With DC Hi-Pot Mode												None*	N
N None*												Industrial Plug	V
B With Burn Down Mode												Universal Plug	U
N None*												Indian Plug*	I
C With Sheath Fault Mode												110V ± 10%, 50Hz AC Input	Q
1 Single, 2S, 4S, 8S												230V ± 10%, 50Hz AC Input*	R
2 Single, 3S, 6S, 9S*												Customized Length of Test Lead Set	Z
Z Customized												50m Test Lead Set	G
F Reserved												35m Test Lead Set	D
N None*												25m Test Lead Set	E
Z customized												20m Test Lead Set	L
F Reserved												15m Test Lead Set	R
N None*												10m Test Lead Set	M
1 Manual Cable Drum												5m Test Lead Set*	T
2 Motorized Cable Drum													

Note: * Standard accessory / feature

#CFL SG 1610 (Order Code: NNC2FNFNTRIN) - Cable Fault Surge Generator with Sheath Fault Location Mode, Surge Sequence of Single / 3S / 6S / 9S, 5m Test Lead Set, 230V ± 10%, 50/60Hz AC Input, Indian Plug.

Generation, Transmission,
Distribution, Industry ...

... there is **SCOPE**
always!

Corporate Office

402, Aarus Chambers, Annex-A,
S.S.Amrutwar Marg, Worli,
Mumbai 400013, INDIA
Phone : +91 22 4344 4244
Fax : +91 22 4344 4242
Email : marketing@scopetnm.com

Works & After Seles

EL 31/11, 'J' BLOCK,
MIDC Bhosari,
Pune 411026, INDIA
Phone : +91 20 6733 3999
Fax : +91 20 6733 3900
Email : works@scopetnm.com

Simple solutions for difficult measurements®

SCOPE
T & M Pvt Ltd